STANDARDS PRESENTATION TO

CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD

PROPOSED STATE STANDARD, TITLE 8, DIVISION 1, CHAPTER 4

Amend Section 4188 to add the following definition in alphabetical order:

§4188. Definitions.

(a) General Definitions.

Classes. The designation "Class-A" with an order means that the rule applies for all kinds of work. The designation "Class-B" means that the order applies unless the nature of the work, type of machinery, or size and shape of material being worked will not permit.

Danger Zone. Any place in or about a machine or piece of equipment where an employee may be struck by or caught between moving parts, caught between moving and stationary objects or parts of the machine, caught between the material and a moving part of the machine, burned by hot surfaces or exposed to electric shock.

Interlock. A device that operates to prevent the operation of a machine while the cover or door of the machine is open or unlocked, and which will also hold the cover or door closed and locked while the machine is in motion.

Presence Sensing Device Initiation. An operating mode of indirect manual initiation of a single stroke by a presence sensing device when it senses that work motions of the operator, related to feeding and/or removing parts, are completed and all parts of the operator's body or hand tools are safely clear of the point of operation.

Press Brake Die, General-Purpose. A die set used to perform common bending and forming operations on a variety of piece parts or products and not designed for a unique or unusual part or product.

Press Brake, General-Purpose. A mechanically or hydraulically operated machine having only one operator at the front of the machine and with a single operating foot control device which permits the operator to exercise full and final control over the movement of the ram.

NOTE: Authority cited: Section 142.3, Labor Code. Reference: Section 142.3, Labor Code.